



COLORADO RENU LOAN ELIGIBLE MEASURES

Measure	Minimum Efficiency Requirement
Air sealing	Pre- and post-installation blower door test
Air-source heat pump	Ducted: ≥ 7.8 HSPF2 / ≥ 15.2 SEER2 / ≥ 11.7 EER2 for split systems Ductless: ≥ 7.8 HSPF2 / ≥ 15.2 SEER2
Battery storage	Must meet local utility requirements
Central Air Conditioning	≥ 15.2 SEER2 / ≥ 12 EER2
Doors	Opaque: U-Factor ≤ 0.17 , SHGC no rating $\leq 1/2$ -Lite: U-Factor ≤ 0.25 , SHGC ≤ 0.25 > 1/2-Lite: U-Factor ≤ 0.30 , SHGC ≤ 0.40
Electrical panel upgrade	Must accompany the installation of a qualifying energy upgrade (e.g. solar PV system, heat pump, etc.)
EV charging station	Level 2
Evaporative cooling	≥ 2500 CFM
Furnace	$\geq 95\%$ AFUE
Geothermal system (water-to-air, closed loop)	≥ 17.1 EER, ≥ 3.6 COP
Geothermal system (water-to-air, open loop)	≥ 21.1 EER, ≥ 4.1 COP
Geothermal system (water-to-water, closed loop)	≥ 16.1 EER, ≥ 3.1 COP
Geothermal system (water-to-water, open loop)	≥ 20.1 EER, ≥ 3.5 COP

Measure	Minimum Efficiency Requirement
Insulation - attic/ceiling	Climate zone 3: R-49 minimum Climate zones 4-7: R-60 minimum Pre- and post-installation blower door test
Insulation - floor	Climate zones 3-4: R-19 minimum Climate zones 5-6: R-30 minimum Climate zone 7: R-38 minimum Pre- and post-installation blower door test
Insulation - wall	R-19 minimum; fill wall cavity where R-value is not possible Pre- and post-installation blower door test
Solar PV	
Water heater (electric heat pump)	UEF \geq 3.30
Water heater (electric)	UEF \geq 0.93
Water heater (gas storage)	UEF \geq 0.86
Water heater (gas tankless)	UEF \geq 0.95
Windows	U-Factor \leq 0.27, SHGC any U-Factor = 0.28, SHGC \geq 0.32 U-Factor = 0.29, SHGC \geq 0.37 U-Factor = 0.30, SHGC \geq 0.42